



Product Data Sheet

Masterlube DX3 ATF Dexron 3

Product Description

Masterlube DX3 is an automatic transmission fluid which is blended from premium quality base oils to meet General Motors Dexron IIIH, Ford Mercon and Allison C-4 specifications.

This product is a high viscosity index fluid containing superior additive technology which provides excellent thermal stability, oxidation resistance and sludge protection.

Specifications and Approvals

Masterlube DX3 meets or exceeds the following specifications:

- Allison C-4
- Caterpillar TO-2
- Denison - Hydraulic Pump Systems
- Ford Mercon
- General Motors Dexron III (H/G/F/E/D/A)
- Holden HN2126
- Mazda M-III
- NissanMatic C
- Sperry Vickers - Hydraulic Pump Systems
- Sunstrand - Hydraulic Pump Systems
- Toyota T
- Volvo 97341

Applications and Benefits

- Smooth gear shifting properties
- Excellent low temperature performance
- Outstanding thermal and oxidation stability

The Oilman Group Pty Ltd
www.oilman.com.au

Head Office: (08) 8262 9399
Adelaide: (08) 8349 9277
Brisbane: (07) 3216 7196
Darwin: 1300 133 783
Melbourne: 1300 133 783
Perth: 1300 133 783

Masterlube DX3 is suitable for all General Motors three, four speed automatic transmissions up to 2006, and many other makes. It may also be used as a power steering fluid and in hydraulic systems, particularly where high temperatures are encountered.

Package Information

200 Litres, 60 Litres, 20 Litres.

Typical Characteristics

Density at 15°C	0.857
Kinematic Viscosity at 40°C, mm ² /s (cSt)	36
Kinematic Viscosity at 100°C, mm ² /s (cSt)	7.1
Viscosity Index	178
Pour Point °C	-49
Flash Point °C	182

Typical Characteristics are average values, and may vary due to normal manufacturing tolerances. The information contained herein is subject to change without notice.