



## Product Data Sheet

# Masterlube 300 20w/50 CF-4/SM

### Product Description

**Masterlube 300** is a versatile and economical high performance diesel engine oil meeting API CF-4/SM standards in diesel/petrol lubrication. It has been specifically formulated as a stay in grade oil to equally perform in engines running on diesel, petrol or LPG, whether turbocharged, or naturally aspirated.

### Specifications and Approvals

**Masterlube 300** meets or exceeds the following specifications:

- API CF-4/SM, CF, SL/SJ
- CCMC D4/G4/PD-2
- Ford ESE-M2C-153E
- Daimler DB 226.1
- US MIL-L-21046, 46152E

### Applications and Benefits

**Masterlube 300** is recommended for use in European, Japanese and pre-1995 US turbocharged and non-turbocharged diesel engines.

It is also suitable for automotive petrol engines and 4 wheel drives due to the high level of detergents and dispersants that provide excellent protection from typical city stop-start operation that promotes acid sludge formation in the engine.

### Package Information

**200 Litres, 20 Litres.**

### Typical Characteristics

Density at 15°C	0.886
Kinematic Viscosity at 40°C, mm <sup>2</sup> /s (cSt)	140
Kinematic Viscosity at 100°C, mm <sup>2</sup> /s (cSt)	17.2
Viscosity Index	129
Sulphated Ash, wt%	1.15
TBN, mgKOH/g	8.9
Pour Point °C	-22
Flash Point °C	225

#### The Oilman Group Pty Ltd

[www.oilman.com.au](http://www.oilman.com.au)

Head Office:	(08) 8262 9399
Adelaide:	(08) 8349 9277
Brisbane:	(07) 3216 7196
Darwin:	1300 133 783
Melbourne:	1300 133 783
Perth:	1300 133 783