



## Product Data Sheet

# Multi Tractor Super 15w/40 GL-4 CE/SF

### Product Description

**Multi Tractor Super** has been formulated to lubricate most systems in agricultural machinery. Being a truly universal oil, it contains special friction additives to satisfy hydraulic and wet brake applications. It is designed to maintain peak performance of agricultural and commercial tractors in a wide range of environments and conditions.

### Specifications and Approvals

**Multi Tractor Super** meets or exceeds the following specifications:

- API CF-4, CE/SF
- API GL-4
- ACEA E2
- Allison C-4
- Caterpillar TO-2
- CCMC D4
- Daimler Benz 227.1, 228.1
- Ford M2C-159B/C, 134D
- John Deere JMD, J20C, J27
- Massey Ferguson MF1139 / 1144 / 1145
- New Holland 82009201/2/3
- Case New Holland MAT3525 / 3526
- ZF TE-ML 06 / 07

### Applications and Benefits

- High oxidation resistance
- Superior soot handling

**Multi Tractor Super** is best suited for main transmission, agricultural hydraulic systems, tractor gearboxes and ancillary equipment. It is also suitable for wet brakes, final drives, power take-offs and hydrostatic steering systems.

### Package Information

200 Litres, 20 Litres.

### Typical Characteristics

Density at 15°C	0.89
Kinematic Viscosity at 40°C, mm <sup>2</sup> /s (cSt)	121
Kinematic Viscosity at 100°C, mm <sup>2</sup> /s (cSt)	14.5
Viscosity Index	122
Flash Point °C	232

Typical Characteristics are average values, and may vary due to normal manufacturing tolerances. The information contained herein is subject to change without notice.

**The Oilman Group Pty Ltd**  
[www.oilman.com.au](http://www.oilman.com.au)

Head Office: (08) 8262 9399  
Adelaide: (08) 8349 9277  
Brisbane: (07) 3216 7196  
Darwin: 1300 133 783  
Melbourne: 1300 133 783  
Perth: 1300 133 783

Fax: (08) 8262 9499  
Fax: (08) 8349 9419  
Fax: (07) 3272 7864