



## Product Data Sheet

# Multi Tractor Trans 10w/30 GL-4

### Product Description

MTT is a superior tractor fluid developed to meet the requirements of modern tractor transmission and hydraulic systems. It is designed to maintain peak performance of agricultural and commercial tractors in a wide range of environments and conditions. Due to a high performance additive package and select base oils, **MTT** reduces Wet Brake and Power Take Off chatter.

### Specifications and Approvals

MTT meets or exceeds the following specifications:

- API GL-4
- Allison Chalmers - 25743 (PF-821XL), 257541 246634 Hyd Trans Fluid
- Allison C-4
- Belarus
- Case (International) MS1204/5, 1206 (Powergard PFT), 1207 (Hy-Trans Plus), 1209 (Hy-Trans Ultra), 1210, JIC 143/44, 145 (TCH Fluid), 185 (TFD Fluid)
- Caterpillar TO-2
- Claas Renault Agric
- CNH MAT 3505, 3525
- Denison HF-0/1/2 (T5D & P46 Pump Only)
- Deutz Hydr Trans Fluid
- Eaton Fuller (Sperry Vickers) 35VQ25, I-280-S, M-2950-S
- Fiat-Hesston AF-87
- Ford New Holland M2C134-B/C/D, M2C86-A/B/C, M2C41-B, M2C48-B/C, M2C53-A, M2C77-A, FNHA 2C-201.00
- IHC B5, B6 Hytrans
- John Deere J27, J20A/B/C/D Hy-Gard, J21A J14A/B/C, JDT303
- Kubota UDT Fluid
- Landini Tractor Hyd Fluid
- Massey Ferguson M1110, M1127A/B, M1129A Permatran, M1135 Permatran III, M1141, M1143, M1145
- Oliver Type 51, 55, 5J, Q1802
- Powerfluid 821 XL
- Type 424
- US MIL-L-2104D, 46167B
- Volvo WB-101/BM CE (Inc. Wet Brakes)
- White Farm Equipment Q-1705, 1722, 1766/B (UTHF), 1802, 1826
- ZF TE-ML 03E, 03F, 05F, 06K, 17E

### Applications and Benefits

This multi functional oil is suitable for tractors and mobile equipment as well as being designed to carry out the following functions:

- Lubricate transmissions, differentials, final drives, hydraulics, power steering, Wet Brakes, Power Take Off clutches and hydrostatic drives.
- Keep systems clean and operating smoothly due to unique filterability properties.
- Provide proper cooling and frictional properties for Wet Brakes and Power Take Off clutches.
- Perform effective lubrication in cold weather applications.

MTT contains a unique seal conditioning agent and foam inhibitor.

### Package Information

1,000 Litres, 200 Litres, 20 Litres.

**The Oilman Group Pty Ltd**  
[www.oilman.com.au](http://www.oilman.com.au)

Head Office: (08) 8262 9399  
Adelaide: (08) 8349 9277  
Brisbane: (07) 3216 7196  
Darwin: 1300 133 783  
Melbourne: 1300 133 783  
Perth: 1300 133 783

## Typical Characteristics

Density at 15°C	0.86
Kinematic Viscosity at 40°C, mm <sup>2</sup> /s (cSt)	59
Kinematic Viscosity at 100°C, mm <sup>2</sup> /s (cSt)	9.8
Viscosity Index	153
Pour Point °C	-40
Flash Point °C	213

Typical Characteristics are average values, and may vary due to normal manufacturing tolerances. The information contained herein is subject to change without notice.