



Product Data Sheet

Slideway Oil ISO 68

Product Description

OCOMA Slideway Oil is a high performance extreme pressure slideway lubricants formulated with an advanced additive package that provides exceptional friction properties on multi-material surfaces such as metal on metal, metal on polymer and polymer on polymer.

OCOMA Slideway Oil allows smooth operation, enhancing machine productivity and accuracy. These products are designed to resist wash out from water soluble cutting fluids, reducing downtime due to expensive repair or replacement.

Applications and Benefits

- Helps eliminate stick slip
- Advanced adhesive properties
- Comprehensive corrosion and rust protection

OCOMA Slideway Oil should be used for lubricating machinery under high loads and pressures such as lathes, milling machines and other equipment with slides and carriage ways. It may also be used in machine tool hydraulic systems.

Package Information

200 Litres.

Typical Characteristics

ISO Grade	68
Kinematic Viscosity at 40°C, mm ² /s (cSt)	68
Kinematic Viscosity at 100°C, mm ² /s (cSt)	8.8
Pour Point °C	-15
Flash Point °C	221
Rust Test. ASTM D665B	Pass

The Oilman Group Pty Ltd
www.oilman.com.au

Head Office: (08) 8262 9399
Adelaide: (08) 8349 9277
Brisbane: (07) 3216 7196
Darwin: 1300 133 783
Melbourne: 1300 133 783
Perth: 1300 133 783

Typical Characteristics are average values, and may vary due to normal manufacturing tolerances. The information contained herein is subject to change without notice.