



## Product Data Sheet

# Super Blue EP-2 Lithium Complex Grease

### Product Description

**Made In USA**

**Super Blue** grease is a premium, lithium complex lubricating grease. This multi-purpose lithium complex grease has a high dropping point in excess of 260°C (500°F), which ensures retention where high temperatures are encountered. This product has been formulated with a special additive package which ensure high film strength, extreme pressure (EP) and anti-wear properties. The high quality virgin base fluids provide excellent natural oxidation inhibition, this combined with effective anti-oxidants as well as corrosion inhibitors provide extra stability under storage and extreme service conditions.

### Meets NLGI Certification GC-LB

The Oilman Group Pty Ltd  
[www.oilman.com.au](http://www.oilman.com.au)

### Package Information

180KG Drum, 20KG Tub, Carton of 20 450gsm Cartridges.

Head Office: (08) 8262 9399  
Adelaide: (08) 8349 9277  
Brisbane: (07) 3216 7196

### Typical Characteristics

NLGI Grade	2
Soap Type	Lithium Complex
Texture	Smooth/Tacky
Worked Penetration, ASTM D-217, 60 strokes	265-295
Dropping Point, ASTM D-2265, °C (°F) Min	260 (500)
Oxidation Stability, ASTM D-942 PSI Drop	5
Wheel Bearing Leakage, ASTM D-1263 Gms	6.0
Rust Test, Bearing Corrosion, ASTM D-1743	Pass
Copper Corrosion, ASTM D-4048, Rating	1b
Water Wash-Out, ASTM D-1264, 79.4°C	5% Max
Oil Separation, ASTM D-1742, % Loss	3.5
Timken OK Load, LB ASTM D-2509	45 Min
Four Ball EP Test, ASTM D-2596	
Weld Point, KG	315 Min
Load Wear Index (LW), KG	45
Four Ball Wear, ASTM D-2266, Scar Dia. Mm, 40 KG	0.60
Base Oil Viscosity	
100°C, cSt	16.5-19.0
40°C, cSt	180-240
100°F, SUS	925-1250
Viscosity Index Min	90

Typical Characteristics are average values, and may vary due to normal manufacturing tolerances.  
The information contained herein is subject to change without notice.