



Product Data Sheet

SuperFleet 15 15w/40 SM/CF

Product Description

SuperFleet 15 is a versatile and economical high performance engine oil meeting API SM/CF standards. It has been specifically formulated as a stay in grade oil to equally perform in engines running on petrol or LPG, whether turbocharged, or naturally aspirated.

Specifications and Approvals

SuperFleet 15 meets or exceeds the following specifications:

- API SM/CF, SL/SJ
- ACEA A3
- CCMC D4/G4/PD-2
- Daimler Benz DB 226.1
- Ford ESE-M2C153E
- US MIL-L-46152E, 2104B

The Oilman Group Pty Ltd
www.oilman.com.au

Head Office: (08) 8262 9399
Adelaide: (08) 8349 9277
Brisbane: (07) 3216 7196
Darwin: 1300 133 783
Melbourne: 1300 133 783
Perth: 1300 133 783

Applications and Benefits

- Outstanding protection against harmful effects of stop-and-go driving
- Minimizes low temperature sludge formation

Is suitable for automotive petrol engines and 4 wheel drives due to the high level of detergents and dispersants that provide excellent protection from typical city stop-start operation that promotes acid sludge formation in the engine

Package Information

200 Litres

Typical Characteristics

Density at 15°C	0.887
Kinematic Viscosity at 40°C, mm ² /s (cSt)	104
Kinematic Viscosity at 100°C, mm ² /s (cSt)	14.1
Viscosity Index	128
Pour Point °C	-36
Flash Point °C	220

Typical Characteristics are average values, and may vary due to normal manufacturing tolerances. The information contained herein is subject to change without notice.