



Product Data Sheet

Synthetic Multi Vehicle Trans 4/5/6/7/8 Speed Automatic Transmissions

Product Description

Synthetic MVT is a new generation multipurpose, full synthetic Automatic Transmission Fluid developed to cover virtually all ATF specifications, with the exception of CVT and Ford "Type F". Designed to meet American, European and Japanese transmissions, Synthetic MVT is the perfect choice for the consumer who does not want to carry multiple drums of products.

Designed to meet and exceed the next generation fuel efficient long life specification fluids. This product has a high viscosity index, contains superior additive technology, which provides outstanding service life span, shift pattern performance, extended clutch life, thermal stability as well as oxidation resistance and sludge control.

Specifications and Approvals

Synthetic MVT meets or exceeds the following specifications and approvals:

- Allison C-4, TES-295, TES-389
- BMW LA-2634, 7045-E, LT-71141, 8072-B
- Chrysler/Dodge/Jeep ATF +3/+4, Mopar AS68RC
- Ford Mercon M, V, LV, SP, FNR5, WSS-M2C922-A1
- GM Dexron VI, IIIH/G, IID/E, T-IV, AW1
- Honda ATF Z-1, DW-1
- Hyundai/Kia SPH-IV, SP-IV/III/II, JWS-3309 T-4, NWS-9638 T-5, RED-1K
- Isuzu ATF II / III
- Idemitsu ATF-HP, K17
- Jaguar Fluid 8432, JLM 20238 / 20292 / 21044 K17, WSS-M2C922-A1
- JASO M315, Class 1A
- JWS/Suzuki 3309, 3317, 3324
- MAN 339A
- Mazda ATF M-V, M-III, Type T-IV, FZ, F-1 JWS3317
- Mercedes Benz 236.15, 236.14, 236.12, 236.11, 236.10, 236.91, 236.9, 236.8, 236.7, 236.6, 236.5, 236.41, 236.3, 236.2
- Mitsubishi SP-III, SP-II, ATF J2/J3
- Nissan 402, Matic - W/S/K/J/D
- Porsche A2
- Renault Matic D2
- SAAB 3309 TIV, AW-1
- Ssang Yong DSIH 5M-66
- Subaru ATF-HP
- Suzuki 3314, 3317
- Toyota D-II, T-IV, T-III, WS
- VW/Audi G 052-025-A2, G 052-055, G 052-162-A1 / A2, G 052-533, G 052-990-A2, G 055-005-A / A2, G 055 025-A2, G 055-540-A2, G US-000-162
- ZF TE-ML 11A / 11B

Applications and Benefits

- Full synthetic provides maximum performance
- Excellent protection against corrosion and wear
- Outstanding long life characteristics
- Reliable under low and high temperatures

The Oilman Group Pty Ltd
www.theoilman.com.au

Head Office: (08) 8262 9399
Adelaide: (08) 8349 9277
Brisbane: (07) 3216 7196
Darwin: 1300 133 783
Melbourne: 1300 133 783
Perth: 1300 133 783

Synthetic MVT is a very versatile fluid and can be used in almost all American, European and Japanese vehicles. It may also be used as a power steering fluid and in hydraulic systems particularly where high temperatures are encountered.

Package Information

200 Litres, 60 Litres, 20 Litres.

Typical Characteristics

Density at 15°C	0.848
Kinematic Viscosity at 40°C, mm ² /s (cSt)	36.81
Kinematic Viscosity at 100°C, mm ² /s (cSt)	6.42
Viscosity Index	152
Pour Point °C	-48
Flash Point °C	210

Typical Characteristics are average values, and may vary due to normal manufacturing tolerances.
The information contained herein is subject to change without notice.